



Pattern	SIZE	Ply Rating	Load Index	Seed Symbol	XL or RF	Sidewall Style	TL or TT	MFS	E-No.	Overall Diam (mm)	Section Width (mm)	Rim Width		Deth
												Measuring (inch)	ermitted (inch)	
PT2			265 / 50	R 20						773	274	8,5	7,5 - 9,5	8,2
PT2	P		285 / 50	R 20						796	287	9	8 - 10	8,2
PT2			215 / 55	R 17						667	222	7	6 - 7,5	8
PT2			225 / 55	R 18						706	231	7	6 - 8	8
PT2			235 / 55	R 18						714	246	7,5	6,5 - 8,5	8
PT2			255 / 55	R 18						736	266	8	7 - 9	8,2
PT2			235 / 55	R 19						742	240	7,5	6,5 - 8,5	8
PT2			245 / 55	R 19						753	250	7,5	7 - 8,5	8
PT1	*	P255	255 / 60	R 15		OW	TL			688	260	7,5	7 - 9	8,1
PT2			215 / 60	R 16			TL			664	220	6,5	6 - 7,5	7,9
PT2			235 / 60	R 16			TL			688	240	7	6,5 - 8,5	7,9
PT2			225 / 60	R 17			TL			704	227	6,5	6 - 8	7,9
PT2			235 / 60	R 17			TL			713	237	7	6,5 - 8,5	8,1
PT1	*		285 / 60	R 17			TL							
PT2			235 / 60	R 18			TL			740	238	7	6,5 - 8,5	7,9
PT2			255 / 60	R 18			TL			762	256	7,5	7 - 9	8,1
PT2			265 / 60	R 18			TL			777	272	8	7,5 - 9,5	8
PT1	*P		285 / 60	R 18			TL			800	289	8,5	8 - 10	8,4
PT2			215 / 65	R 16			TL			689	219	6,5	6 - 7,5	7,9
PT2			225 / 65	R 17			TL			725	227	6,5	6 - 8	7,9
PT2			235 / 65	R 17			TL			737	241	7	6,5 - 8,5	8,1
PT2			265 / 65	R 17			TL			777	272	8	7,5 - 9,5	8
PT2			275 / 65	R 17			TL			789	280	8	7,5 - 9,5	8,1
PT2			205 / 70	R 15			TL			669	212	6	5 - 7	8,1
PT2			215 / 70	R 15			TL							
PT2			215 / 70	R 16			TL			708	223	6,5	5,5 - 7	8,2
PT2			245 / 70	R 16			TL			749	243	7	6,5 - 8	8,4
PT1	*		265 / 70	R 15			TL			754	270	8	7 - 9	8,6
PT2			265 / 70	R 16			TL			778	280	8	7 - 9	8,6
PT1	*		275 / 70	R 16			TL			793	280	8	7 - 9	8,6